



ROMA WELDED FEET DIMENSIONS (mm)					
MODEL (COLUMNS)		2 COLUMN	3 COLUMN	4 COLUMN	6 COLUMN
Width of radiator		(No. of sections x 46) + 30			
Section depth		66	107	148	230
Section width (tube + space)		46	46	46	46
Back wall to front of rad	(A)	96	137	178	260
Back wall to pipe centres	Side entry (B)	63	84	104	145
Tapping centres	Side entry (C)	Width of rad			
Pipe centres	Side entry	Tapping centres plus valves			
Bracket positions	Top (Dt)	70			
	Bottom (Db)	Adjustable			
Welded feet	(E)	100			
Tappings		1/2"			

2 COLUMN WELDED FEET WEIGHTS AND VOLUMES (per section)	
Model height mm	700
Dry weight (A) Kg	0.91
Water content (B) Litres	0.65
Working weight (A+B) Kg	1.56
Outputs: Watts ΔT=50k	44

3 COLUMN WELDED FEET WEIGHTS AND VOLUMES (per section)	
Model height mm	700
Dry weight (A) Kg	1.51
Water content (B) Litres	0.95
Working weight (A+B) Kg	2.46
Outputs: Watts ΔT=50k	61

4 COLUMN WELDED FEET WEIGHTS AND VOLUMES (per section)				
Model height mm	400	600	700	1000
Dry weight (A) Kg	0.94	1.52	1.81	2.69
Water content (B) Litres	0.78	1.09	1.25	1.73
Working weight (A+B) Kg	1.72	2.61	3.06	4.42
Outputs: Watts ΔT=50k	43	69	82	120

6 COLUMN WELDED FEET WEIGHTS AND VOLUMES (per section)				
Model height mm	400	600	700	1000
Dry weight (A) Kg	1.60	2.47	2.91	4.21
Water content (B) Litres	1.16	1.63	1.87	2.59
Working weight (A+B) Kg	2.76	4.10	4.78	6.80
Outputs: Watts ΔT=50k	62	100	119	175

TEMPERATURE			
FACTORS FOR DIFFERENCES BETWEEN MEAN WATER TEMPERATURE AND ROOM TEMPERATURE IN °C AND °F OTHER THAN 50 °C (90 °F)			
5 °C	0.050	10 °F	0.057
10 °C	0.123	20 °F	0.142
15 °C	0.209	30 °F	0.240
20 °C	0.304	40 °F	0.348
25 °C	0.406	50 °F	0.466
30 °C	0.515	60 °F	0.590
35 °C	0.629	70 °F	0.721
40 °C	0.748	80 °F	0.858
45 °C	0.872	90 °F	1.000
50 °C	1.000	100 °F	1.147
55 °C	1.132	110 °F	1.298
60 °C	1.267	120 °F	1.454
65 °C	1.406	130 °F	1.613
70 °C	1.549	140 °F	1.776
75 °C	1.694		

TO APPLY THE FACTORS SHOWN IN THE TABLE TO OUR QUOTED OUTPUTS. MULTIPLY THE QUOTED OUTPUT BY THE CHOSEN OPERATING FACTOR TO GIVE THE OUTPUT

ADDITIONAL INFORMATION	
Material	Steel
Steel tube diameter	25mm
Steel thickness	1.25mm
Maximum working pressure	10 bar/1000 kPa
Mechanical Strength Test Pressure	13 bar/1300 kPa
Maximum working temperature	95°C

Note: no diverter fitted